



CPX Septic 3200L

Robust, low buildt septic tank with large sedimentation volume and 3 chambers that provide an extra long sedimentation distance. The separation capacity is very high (0,06g). The flexible, robust design makes CPX Septic tank suitable for most ground conditions and allows the in- and out lets to be placed on both short and long sides of the septic tank.

CPX Septic tank 3200 is suitable for individual sewage systems with grey and black water. The septic tank can be used with or without extension neck and lockable, childproof lid is included.

Approved according to EN12566," Sewage treatment plant up to 50PE, factory made septic tanks" with third party approval from Swedish RISE.

CPX Septic tank 3200L is optimized for transport as a part of our ambition to minimize environmental effects and manufactured from age-resistant and 100% recyclable plastic.

Also available in a version with integrated pump well and pump if you need to pump the water to the ground bed/infiltration.

Art.nr: 23032



Approximate size

Specifications	
Material	PE
Bottom shape	Straight
Lid type	
Color	Black
Volume (L)	3200
Length (mm)	2600
Width (mm)	2350
Height (mm)	910
Weight (kg)	270
Sludge volume (L)	1650
Wet volume (L)	3200
Tollstatistical code	3925100000
Climate impact (kg CO2-ekv.)	686
Characteristics	
 Customizable containers	 Recyclable
 Wide temperature range	 Chemical resistance
 Leak test	 Logistics solutions
 Easy to clean	

