



CPX Septic 4200L

Robust, low buildt septic tank with large sedimentation volume and 3 chambers that provide an extra long sedimentation distance. The separation capacity is very high (0,06g). The flexible, robust design makes CPX Septic tank suitable for most ground conditions and allows the in- and out lets to be placed on both short and long sides of the septic tank.

CPX Septic tank 4200 is suitable for individual sewage systems with grey and black water. The septic tank can be used with or without extension neck and lockable, childproof lid is included.

Approved according to EN12566, "Sewage treatment plant up to 50PE, factory made septic tanks" with third party approval from Swedish RISE.

CPX Septic tank 4200L is optimized for transport as a part of our ambition to minimize environmental effects and manufactured from age-resistant and 100% recyclable plastic.

Also available in a version with integrated pump well and pump if you need to pump the water to the ground bed/infiltration.

Art.nr: 23042



Approximate size

Specifications	
Material	PE
Bottom shape	Straight
Lid type	
Color	Black
Volume (L)	4200
Length (mm)	2600
Width (mm)	2350
Height (mm)	1200
Weight (kg)	305
Sludge volume (L)	2100
Wet volume (L)	4200
Tollstatistical code	3925100000
GTIN	7090046760924
Characteristics	
Climate impact (kg CO2-ekv.)	755
 Customizable containers  Recyclable  Chemical resistance  Leak test  Logistics solutions  Easy to clean	

